

Maintenance: Normal Service 7500 MI or 12000 KM

Inspect

Engine Mount.....
Rear Engine Mount. 4MATIC models only, at first interval only.

Lubricate

Hinge, Hood.....
(E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

Fluid - M/T.....
Gear Lubricant, Special
One time service only.
(E) Oil.....
At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.
(E) Oil Filter, Engine.....

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 15000 MI or 24000 KM

Check

Brakes and Traction Control.....
Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.
 Clutch, M/T.....
Check operation.
 Heating and Air Conditioning.....
Check operation and Freon (R) charge.

Clean

Antenna Mast.....
 Tape Player.....
Tape Deck Head.

Inspect/Adjust

Drive Belt.....
 Parking Brake System.....

Inspect

Accessories and Optional Equipment.....
 Battery.....
 Brake Fluid.....
Hydraulic Brake Fluid, SAE J1703, DOT-4
 Clutch Fluid.....
Hydraulic Brake Fluid, SAE J1703, DOT-4
 Convertible Top.....
Check level of hydraulic system, check operation of locking lug.
 Coolant.....
Ethylene Glycol Coolant; Mix with water to desired freeze protection.
Check degree of antifreeze protection.
 (S) Fluid - A/T.....
DEXRON-II (R) Automatic Transmission Fluid
 Fluid - Differential.....
Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.
4MATIC models, also check front differential.
 Fluid - M/T.....
Gear Lubricant, Special
 Fluid - Transfer Case.....
DEXRON-II (R) Automatic Transmission Fluid
4MATIC models.
 (E) Fuel Supply Line.....
Check fuel tank, lines.
 Power Steering Fluid.....
Power Steering Fluid
Inspect condition of lines and hoses.
 Seat Belt Systems.....
 Spark Plug.....
Replace as necessary.
 Steering.....
Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.
 Suspension Control Module.....
Special Lubrication Fluid.
Level Control.
 Wiper and Washer Systems.....

Lubricate

Body and Frame.....
 Hinge, Hood.....
 Sunroof Track.....

(E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

(E) Oil.....
At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.
(E) Oil Filter, Engine.....
Wiper Blade.....

Rotate

Wheels.....

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 22500 MI or 36000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement

(E) = Emission Warranty Requirement

(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 30000 MI or 48000 KM

Check

| | |
|---|-------|
| Brakes and Traction Control..... | _____ |
| <i>Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.</i> | |
| Clutch, M/T..... | _____ |
| <i>Check operation.</i> | |
| Heating and Air Conditioning..... | _____ |
| <i>Check operation and Freon (R) charge.</i> | |

Clean

| | |
|------------------------|-------|
| Antenna Mast..... | _____ |
| Tape Player..... | _____ |
| <i>Tape Deck Head.</i> | |

Inspect/Adjust

| | |
|---------------------------|-------|
| Drive Belt..... | _____ |
| Parking Brake System..... | _____ |

Inspect

| | |
|---|-------|
| Accessories and Optional Equipment..... | _____ |
| Battery..... | _____ |
| Clutch Disc, M/T..... | _____ |
| Clutch Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Convertible Top..... | _____ |
| <i>Check level of hydraulic system, check operation of locking lug.</i> | |
| Coolant..... | _____ |
| <i>Ethylene Glycol Coolant; Mix with water to desired freeze protection.</i> | |
| <i>Check degree of antifreeze protection.</i> | |
| Drive/Propeller Shaft..... | _____ |
| <i>Drive Shaft Flex Discs.</i> | |
| Fluid - Differential..... | _____ |
| <i>Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.</i> | |
| <i>4MATIC models, also check front differential.</i> | |
| Fluid - Transfer Case..... | _____ |
| <i>DEXRON-II (R) Automatic Transmission Fluid</i> | |
| <i>4MATIC models.</i> | |
| (E) Fuel Supply Line..... | _____ |
| <i>Check fuel tank, lines.</i> | |
| Power Steering Fluid..... | _____ |
| <i>Power Steering Fluid</i> | |
| <i>Inspect condition of lines and hoses.</i> | |
| Seat Belt Systems..... | _____ |
| Steering..... | _____ |
| <i>Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorquing mounting bolts.</i> | |
| Suspension Control Module..... | _____ |
| <i>Special Lubrication Fluid.</i> | |
| <i>Level Control.</i> | |
| Wiper and Washer Systems..... | _____ |

Lubricate

| | |
|--|-------|
| Body and Frame..... | _____ |
| Hinge, Hood..... | _____ |
| Sunroof Track..... | _____ |
| (E) Throttle Cable/Linkage..... | _____ |
| <i>Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10</i> | |
| <i>At least twice a year.</i> | |

Replace

| | | |
|-----|--|-------|
| (E) | Air Filter Element..... | _____ |
| | Air Injection Filter..... | _____ |
| | <i>If equipped.</i> | |
| | Brake Fluid..... | _____ |
| | <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| (S) | Fluid - A/T..... | _____ |
| | Fluid - M/T..... | _____ |
| (S) | Fluid Filter - A/T..... | _____ |
| (E) | Oil..... | _____ |
| | <i>At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.</i> | |
| (E) | Oil Filter, Engine..... | _____ |
| (E) | Spark Plug..... | _____ |
| | Wiper Blade..... | _____ |

Rotate

| | |
|-------------|-------|
| Wheels..... | _____ |
|-------------|-------|

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 37500 MI or 60000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement

(E) = Emission Warranty Requirement

(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 45000 MI or 72000 KM

Check

- Brakes and Traction Control.....
Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.
- Clutch, M/T.....
Check operation.
- Heating and Air Conditioning.....
Check operation and Freon (R) charge.

Clean

- Antenna Mast.....
- Tape Player.....
Tape Deck Head.

Inspect/Adjust

- Drive Belt.....
- Parking Brake System.....

Inspect

- Accessories and Optional Equipment.....
- Battery.....
- Brake Fluid.....
Hydraulic Brake Fluid, SAE J1703, DOT-4
- Clutch Fluid.....
Hydraulic Brake Fluid, SAE J1703, DOT-4
- Convertible Top.....
Check level of hydraulic system, check operation of locking lug.
- (S) Fluid - A/T.....
DEXRON-II (R) Automatic Transmission Fluid
- Fluid - Differential.....
Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.
4MATIC models, also check front differential.
- Fluid - M/T.....
Gear Lubricant, Special
- Fluid - Transfer Case.....
DEXRON-II (R) Automatic Transmission Fluid
4MATIC models.
- (E) Fuel Supply Line.....
Check fuel tank, lines.
- Power Steering Fluid.....
Power Steering Fluid
Inspect condition of lines and hoses.
- Seat Belt Systems.....
- Spark Plug.....
Replace as necessary.
- Steering.....
Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.
- Suspension Control Module.....
Special Lubrication Fluid.
Level Control.
- Wiper and Washer Systems.....

Lubricate

- Body and Frame.....
- Hinge, Hood.....
- Sunroof Track.....
- (E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

- Coolant.....
- (E) Oil.....
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine.....
- Wiper Blade.....

Rotate

- Wheels.....

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 52500 MI or 84000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement

(E) = Emission Warranty Requirement

(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 60000 MI or 96000 KM

Check

| | |
|---|-------|
| Brakes and Traction Control..... | _____ |
| <i>Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.</i> | |
| Clutch, M/T..... | _____ |
| <i>Check operation.</i> | |
| Heating and Air Conditioning..... | _____ |
| <i>Check operation and Freon (R) charge.</i> | |

Clean

| | |
|------------------------|-------|
| Antenna Mast..... | _____ |
| Tape Player..... | _____ |
| <i>Tape Deck Head.</i> | |

Inspect/Adjust

| | |
|---------------------------|-------|
| Drive Belt..... | _____ |
| Parking Brake System..... | _____ |

Inspect

| | |
|---|-------|
| Accessories and Optional Equipment..... | _____ |
| Battery..... | _____ |
| Clutch Disc, M/T..... | _____ |
| Clutch Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Convertible Top..... | _____ |
| <i>Check level of hydraulic system, check operation of locking lug.</i> | |
| Coolant..... | _____ |
| <i>Ethylene Glycol Coolant; Mix with water to desired freeze protection.</i> | |
| <i>Check degree of antifreeze protection.</i> | |
| Drive/Propeller Shaft..... | _____ |
| <i>Drive Shaft Flex Discs.</i> | |
| Fluid - Differential..... | _____ |
| <i>Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.</i> | |
| <i>4MATIC models, also check front differential.</i> | |
| Fluid - Transfer Case..... | _____ |
| <i>DEXRON-II (R) Automatic Transmission Fluid</i> | |
| <i>4MATIC models.</i> | |
| (E) Fuel Supply Line..... | _____ |
| <i>Check fuel tank, lines.</i> | |
| Power Steering Fluid..... | _____ |
| <i>Power Steering Fluid</i> | |
| <i>Inspect condition of lines and hoses.</i> | |
| Seat Belt Systems..... | _____ |
| Steering..... | _____ |
| <i>Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.</i> | |
| Suspension Control Module..... | _____ |
| <i>Special Lubrication Fluid.</i> | |
| <i>Level Control.</i> | |
| Wiper and Washer Systems..... | _____ |

Lubricate

| | |
|--|-------|
| Body and Frame..... | _____ |
| Hinge, Hood..... | _____ |
| Sunroof Track..... | _____ |
| (E) Throttle Cable/Linkage..... | _____ |
| <i>Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10</i> | |
| <i>At least twice a year.</i> | |

Replace

| | | |
|-----|--|-------|
| (E) | Air Filter Element..... | _____ |
| | Air Injection Filter..... | _____ |
| | <i>If equipped.</i> | |
| | Brake Fluid..... | _____ |
| | <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| (S) | Fluid - A/T..... | _____ |
| | Fluid - M/T..... | _____ |
| (S) | Fluid Filter - A/T..... | _____ |
| (E) | Fuel Filter..... | _____ |
| (E) | Oil..... | _____ |
| | <i>At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.</i> | |
| (E) | Oil Filter, Engine..... | _____ |
| (E) | Oxygen Sensor..... | _____ |
| (E) | Spark Plug..... | _____ |
| | Wiper Blade..... | _____ |

Rotate

| | |
|-------------|-------|
| Wheels..... | _____ |
|-------------|-------|

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 67500 MI or 108000 KM

Lubricate

- Hinge, Hood.....
- (E) Throttle Cable/Linkage.....
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil.....
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine.....

(S) = Service Warranty Requirement

(E) = Emission Warranty Requirement

(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 75000 MI or 120000 KM

Check

| | |
|---|-------|
| Brakes and Traction Control..... | _____ |
| <i>Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.</i> | |
| Clutch, M/T..... | _____ |
| <i>Check operation.</i> | |
| Heating and Air Conditioning..... | _____ |
| <i>Check operation and Freon (R) charge.</i> | |

Clean

| | |
|------------------------|-------|
| Antenna Mast..... | _____ |
| Tape Player..... | _____ |
| <i>Tape Deck Head.</i> | |

Inspect/Adjust

| | |
|---------------------------|-------|
| Drive Belt..... | _____ |
| Parking Brake System..... | _____ |

Inspect

| | |
|---|-------|
| Accessories and Optional Equipment..... | _____ |
| Battery..... | _____ |
| Brake Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Clutch Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Convertible Top..... | _____ |
| <i>Check level of hydraulic system, check operation of locking lug.</i> | |
| Coolant..... | _____ |
| <i>Ethylene Glycol Coolant; Mix with water to desired freeze protection.</i> | |
| <i>Check degree of antifreeze protection.</i> | |
| (S) Fluid - A/T..... | _____ |
| <i>DEXRON-II (R) Automatic Transmission Fluid</i> | |
| Fluid - Differential..... | _____ |
| <i>Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.</i> | |
| <i>4MATIC models, also check front differential.</i> | |
| Fluid - M/T..... | _____ |
| <i>Gear Lubricant, Special</i> | |
| Fluid - Transfer Case..... | _____ |
| <i>DEXRON-II (R) Automatic Transmission Fluid</i> | |
| <i>4MATIC models.</i> | |
| (E) Fuel Supply Line..... | _____ |
| <i>Check fuel tank, lines.</i> | |
| Power Steering Fluid..... | _____ |
| <i>Power Steering Fluid</i> | |
| <i>Inspect condition of lines and hoses.</i> | |
| Seat Belt Systems..... | _____ |
| Spark Plug..... | _____ |
| <i>Replace as necessary.</i> | |
| Steering..... | _____ |
| <i>Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.</i> | |
| Suspension Control Module..... | _____ |
| <i>Special Lubrication Fluid.</i> | |
| <i>Level Control.</i> | |
| Wiper and Washer Systems..... | _____ |

Lubricate

| | |
|---------------------|-------|
| Body and Frame..... | _____ |
| Hinge, Hood..... | _____ |
| Sunroof Track..... | _____ |

(E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

(E) Oil.....
At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.
(E) Oil Filter, Engine.....
Wiper Blade.....

Rotate

Wheels.....

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 82500 MI or 132000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 90000 MI or 144000 KM

Check

- Brakes and Traction Control.....
Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.
- Clutch, M/T.....
Check operation.
- Heating and Air Conditioning.....
Check operation and Freon (R) charge.

Clean

- Antenna Mast.....
- Tape Player.....
Tape Deck Head.

Inspect/Adjust

- Drive Belt.....
- Parking Brake System.....

Inspect

- Accessories and Optional Equipment.....
- Battery.....
- Clutch Disc, M/T.....
- Clutch Fluid.....
Hydraulic Brake Fluid, SAE J1703, DOT-4
- Convertible Top.....
Check level of hydraulic system, check operation of locking lug.
- Drive/Propeller Shaft.....
Drive Shaft Flex Discs.
- Fluid - Differential.....
Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.
4MATIC models, also check front differential.
- Fluid - Transfer Case.....
DEXRON-II (R) Automatic Transmission Fluid
4MATIC models.
- (E) Fuel Supply Line.....
Check fuel tank, lines.
- Power Steering Fluid.....
Power Steering Fluid
Inspect condition of lines and hoses.
- Seat Belt Systems.....
- Steering.....
Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.
- Suspension Control Module.....
Special Lubrication Fluid.
Level Control.
- Wiper and Washer Systems.....

Lubricate

- Body and Frame.....
- Hinge, Hood.....
- Sunroof Track.....
- (E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

- (E) Air Filter Element.....
- Air Injection Filter.....
If equipped.

| | |
|--|-------|
| Brake Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Coolant..... | _____ |
| (S) Fluid - A/T..... | _____ |
| Fluid - M/T..... | _____ |
| (S) Fluid Filter - A/T..... | _____ |
| (E) Oil..... | _____ |
| <i>At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.</i> | |
| (E) Oil Filter, Engine..... | _____ |
| (E) Spark Plug..... | _____ |
| Wiper Blade..... | _____ |

Rotate

| | |
|-------------|-------|
| Wheels..... | _____ |
|-------------|-------|

(S) = Service Warranty Requirement

(E) = Emission Warranty Requirement

(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 97500 MI or 156000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement

(E) = Emission Warranty Requirement

(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 105000 MI or 168000 KM

Check

| | |
|---|-------|
| Brakes and Traction Control..... | _____ |
| <i>Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.</i> | |
| Clutch, M/T..... | _____ |
| <i>Check operation.</i> | |
| Heating and Air Conditioning..... | _____ |
| <i>Check operation and Freon (R) charge.</i> | |

Clean

| | |
|------------------------|-------|
| Antenna Mast..... | _____ |
| Tape Player..... | _____ |
| <i>Tape Deck Head.</i> | |

Inspect/Adjust

| | |
|---------------------------|-------|
| Drive Belt..... | _____ |
| Parking Brake System..... | _____ |

Inspect

| | |
|---|-------|
| Accessories and Optional Equipment..... | _____ |
| Battery..... | _____ |
| Brake Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Clutch Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Convertible Top..... | _____ |
| <i>Check level of hydraulic system, check operation of locking lug.</i> | |
| Coolant..... | _____ |
| <i>Ethylene Glycol Coolant; Mix with water to desired freeze protection.</i> | |
| <i>Check degree of antifreeze protection.</i> | |
| (S) Fluid - A/T..... | _____ |
| <i>DEXRON-II (R) Automatic Transmission Fluid</i> | |
| Fluid - Differential..... | _____ |
| <i>Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.</i> | |
| <i>4MATIC models, also check front differential.</i> | |
| Fluid - M/T..... | _____ |
| <i>Gear Lubricant, Special</i> | |
| Fluid - Transfer Case..... | _____ |
| <i>DEXRON-II (R) Automatic Transmission Fluid</i> | |
| <i>4MATIC models.</i> | |
| (E) Fuel Supply Line..... | _____ |
| <i>Check fuel tank, lines.</i> | |
| Power Steering Fluid..... | _____ |
| <i>Power Steering Fluid</i> | |
| <i>Inspect condition of lines and hoses.</i> | |
| Seat Belt Systems..... | _____ |
| Spark Plug..... | _____ |
| <i>Replace as necessary.</i> | |
| Steering..... | _____ |
| <i>Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.</i> | |
| Suspension Control Module..... | _____ |
| <i>Special Lubrication Fluid.</i> | |
| <i>Level Control.</i> | |
| Wiper and Washer Systems..... | _____ |

Lubricate

| | |
|---------------------|-------|
| Body and Frame..... | _____ |
| Hinge, Hood..... | _____ |
| Sunroof Track..... | _____ |

(E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

(E) Oil.....
At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.
(E) Oil Filter, Engine.....
Wiper Blade.....

Rotate

Wheels.....

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 112500 MI or 180000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 120000 MI or 192000 KM

Check

| | |
|---|-------|
| Brakes and Traction Control..... | _____ |
| <i>Clean brake discs and pads, road test system. Adjust parking brake except 140 chassis.</i> | |
| Clutch, M/T..... | _____ |
| <i>Check operation.</i> | |
| Heating and Air Conditioning..... | _____ |
| <i>Check operation and Freon (R) charge.</i> | |

Clean

| | |
|------------------------|-------|
| Antenna Mast..... | _____ |
| Tape Player..... | _____ |
| <i>Tape Deck Head.</i> | |

Inspect/Adjust

| | |
|---------------------------|-------|
| Drive Belt..... | _____ |
| Parking Brake System..... | _____ |

Inspect

| | |
|---|-------|
| Accessories and Optional Equipment..... | _____ |
| Battery..... | _____ |
| Clutch Disc, M/T..... | _____ |
| Clutch Fluid..... | _____ |
| <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| Convertible Top..... | _____ |
| <i>Check level of hydraulic system, check operation of locking lug.</i> | |
| Coolant..... | _____ |
| <i>Ethylene Glycol Coolant; Mix with water to desired freeze protection.</i> | |
| <i>Check degree of antifreeze protection.</i> | |
| Drive/Propeller Shaft..... | _____ |
| <i>Drive Shaft Flex Discs.</i> | |
| Fluid - Differential..... | _____ |
| <i>Gear Oil, API Service GL-5 or Special Lubricant for Limited Differentials; Mercedes-Benz Part No. 000 583 09 04.</i> | |
| <i>4MATIC models, also check front differential.</i> | |
| Fluid - Transfer Case..... | _____ |
| <i>DEXRON-II (R) Automatic Transmission Fluid</i> | |
| <i>4MATIC models.</i> | |
| (E) Fuel Supply Line..... | _____ |
| <i>Check fuel tank, lines.</i> | |
| Power Steering Fluid..... | _____ |
| <i>Power Steering Fluid</i> | |
| <i>Inspect condition of lines and hoses.</i> | |
| Seat Belt Systems..... | _____ |
| Steering..... | _____ |
| <i>Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.</i> | |
| Suspension Control Module..... | _____ |
| <i>Special Lubrication Fluid.</i> | |
| <i>Level Control.</i> | |
| Wiper and Washer Systems..... | _____ |

Lubricate

| | |
|--|-------|
| Body and Frame..... | _____ |
| Hinge, Hood..... | _____ |
| Sunroof Track..... | _____ |
| (E) Throttle Cable/Linkage..... | _____ |
| <i>Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10</i> | |
| <i>At least twice a year.</i> | |

Replace

| | | |
|-----|--|-------|
| (E) | Air Filter Element..... | _____ |
| | Air Injection Filter..... | _____ |
| | <i>If equipped.</i> | |
| | Brake Fluid..... | _____ |
| | <i>Hydraulic Brake Fluid, SAE J1703, DOT-4</i> | |
| (S) | Fluid - A/T..... | _____ |
| | Fluid - M/T..... | _____ |
| (S) | Fluid Filter - A/T..... | _____ |
| (E) | Fuel Filter..... | _____ |
| (E) | Oil..... | _____ |
| | <i>At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.</i> | |
| (E) | Oil Filter, Engine..... | _____ |
| (E) | Oxygen Sensor..... | _____ |
| (E) | Spark Plug..... | _____ |
| | Wiper Blade..... | _____ |

Rotate

| | |
|-------------|-------|
| Wheels..... | _____ |
|-------------|-------|

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 127500 MI or 204000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement

(E) = Emission Warranty Requirement

(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 135000 MI or 216000 KM

Check

Heating and Air Conditioning.....
Check operation and Freon (R) charge.

Clean

Antenna Mast.....
 Tape Player.....
Tape Deck Head.

Inspect/Adjust

Drive Belt.....
 Parking Brake System.....

Inspect

Battery.....
 Brake Fluid.....
Hydraulic Brake Fluid, SAE J1703, DOT-4
 Convertible Top.....
Check level of hydraulic system, check operation of locking lug.
 Coolant.....
Ethylene Glycol Coolant; Mix with water to desired freeze protection.
Check degree of antifreeze protection.
 (S) Fluid - A/T.....
DEXRON-II (R) Automatic Transmission Fluid
 Fluid - M/T.....
Gear Lubricant, Special
 Power Steering Fluid.....
Power Steering Fluid
Inspect condition of lines and hoses.
 Seat Belt Systems.....
 Spark Plug.....
Replace as necessary.
 Steering.....
Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.
 Wiper and Washer Systems.....

Lubricate

Hinge, Hood.....
 Sunroof Track.....
 (E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

(E) Oil.....
At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.
 (E) Oil Filter, Engine.....
 Wiper Blade.....

Rotate

Wheels.....

 (S) = Service Warranty Requirement
 (E) = Emission Warranty Requirement
 (B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 142500 MI or 228000 KM

Lubricate

- Hinge, Hood..... _____
- (E) Throttle Cable/Linkage..... _____
- Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10*
- At least twice a year.*

Replace

- (E) Oil..... _____
- At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.*
- (E) Oil Filter, Engine..... _____

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(B) = Both Service and Emission Warranty Requirement

Maintenance: Normal Service 150000 MI or 240000 KM

Check

Heating and Air Conditioning.....
Check operation and Freon (R) charge.

Clean

Antenna Mast.....
 Tape Player.....
Tape Deck Head.

Inspect/Adjust

Drive Belt.....
 Parking Brake System.....

Inspect

Battery.....
 Brake Fluid.....
Hydraulic Brake Fluid, SAE J1703, DOT-4
 Clutch Disc, M/T.....
 Convertible Top.....
Check level of hydraulic system, check operation of locking lug.
 Coolant.....
Ethylene Glycol Coolant; Mix with water to desired freeze protection.
Check degree of antifreeze protection.
 Drive/Propeller Shaft.....
Drive Shaft Flex Discs.
 Fluid - M/T.....
Gear Lubricant, Special
 Power Steering Fluid.....
Power Steering Fluid
Inspect condition of lines and hoses.
 Seat Belt Systems.....
 Steering.....
Inspect linkage (Front Axle, Steering Linkage And Boots), check freeplay, retorque mounting bolts.
 Wiper and Washer Systems.....

Lubricate

Hinge, Hood.....
 Sunroof Track.....
 (E) Throttle Cable/Linkage.....
Special Lubricant Fluid - Mercedes-Benz Part No. 000 989 91 03 10
At least twice a year.

Replace

(E) Air Filter Element.....
 (S) Fluid - A/T.....
 (S) Fluid Filter - A/T.....
 (E) Oil.....
At least once a year if year-round multigrade oil is used. Otherwise, at least every spring and fall.
 (E) Oil Filter, Engine.....
 (E) Spark Plug.....
 Wiper Blade.....

Rotate

Wheels.....

(B) = Both Service and Emission Warranty Requirement