

Display Document

Sales designation:	Vehicle ident. number:	Engine number:	Automatic transmission:	Gr.:	Entry:	Mod.Y.:	Op. no.:
ML 320	WDB163154*	112.942	722662	47.10			

SI47.10-P-0005GH

Service information: Fuel pump replacement

Full-size view

Validity OFF

Page: 2 / 3

SI47.10-P-0005GH	Service information: Fuel pump replacement	6.4.01
------------------	--	--------

MODEL 163.136 #A up to 125801,
163.136 #X up to 716853
with **ENGINE** 111.977

MODEL 163.154 #A up to 266446,
163.154 #X up to 716524
with **ENGINE** 112.942

MODEL 163.172 #A up to 265965,
163.172 #X up to 716531
with **ENGINE** 113.942

MODEL 163.174 #A up to 266484 with **ENGINE** 113.981

i With the introduction of fuel pump, part nos. **163 470 27 94** and **163 470 28 94**, please note:

i When replacing the fuel pump, the fuel filter must be replaced only if the vehicle is not already equipped with the larger fuel filter with pressure regulator.

If the vehicle has not previously been retrofitted (during maintenance or service) with fuel filter with pressure regulator (FFR), part no. **163 477 05 01**, then this retrofit **must** be performed at time of fuel pump replacement.

Add.

Document

What is

Document:

Level:

Menu

Help

Previous

Screen

Display Document

Sales designation: **ML 320** Vehicle ident. number: **WDB163154*** Engine number: **112.942** Automatic transmission: **722662** Gr.: **47.10** Entry: Mod.Y.: Op. no.:

SI47.10-P-0005GH

Service information: Fuel pump replacement

Full-size view

Validity OFF




Page:

3/ 3

(1111), part no. 100 111 00 01, then the return must be performed at time of fuel pump replacement.

Operation no. of operation texts or standard texts and flat rates

Sector	Op. no.	Operation text	Time	Acc. no.	Code
P	023431	INSTALL SUPPLEMENTAL LINES FOR LARGE CAPACITY FUEL FILTER WITH PRESSURE REGULATOR DURING FUEL PUMP REPLACEMENT	002 AW / 0.2 h	09001 88	
P	075730	REPLACE FUEL PUMP	020 AW / 1.7 h		
P	075563	REPLACE FUEL FILTER WITH PRESSURE REGULATOR	011 AW / 0.9 h		

	Install		
 Danger!	Risk of explosion as a result of fuel vapors igniting. Risk of poisoning as a result of inhaling fuel vapors and open handling of fuel. Risk of injury as a result of fuel splashing into eyes	No fire, naked flame or smoking. Avoid the creation of sparks. Pour fuels only into the canisters provided for this purpose, and store in such canisters. Wear protective gloves and, if necessary, eye protection when handling fuel	AS47.00-Z-0001-01A
1  AP	Replace fuel filter with pressure regulator		AP47.20-P-0780GH

Add.

Document

What is

Document:

1

Level:

1

Menu

Help

Previous

Screen